



WL1680	WL16120T
WL1680T	VL12P1696

General Description

WiPath produces a range of LED moving message displays with integrated intelligent paging receivers able to be deployed anywhere on a local area or wide area paging network.

These LED displays are used for a wide variety of messaging and information purposes including campus emergency mass alerting, information display and for specialized applications such as nursecall.

Applications

Emergency Mass Alert
Dispatch Centre Message Monitoring

Information Displays
Public Information

Nursecall Systems
Factory Alerts

Features

Available in 1, 2 and 4 lines (to order)
Indoor and outdoor models available
Very large capcode capacity
Relay control outputs capcode & message activated (option)

Date/Time display (option)
Paging receiver integrated -pocsag and Flex
Display and alerting functions controlled by message
Receivers available for most paging bands

Specifications

	WL1680R	WL160T	WL16120R	VL12P1696
Type	Indoor	Indoor	Indoor	Outdoor
Colour	Red	Tricolour	Red	Red
Resolution	16x80	16x80	16x120	16x96
No.Lines	2	2	2	2
No.Char/line	16/8	16/8	24/12	20/12
Pitch (mm)	7.62	7.62	7.62	12
Physical (mm)	670x165x60	670x165x60	1000x165x60	1220x250x150
(in.)	~26x7x3	~26x7x3	~39x7x3	~48x10x6
Power (VAC)	100-240VAC	100-240VAC	100-240VAC	100-240VAC