

Unication Alpha Elite Pager Specification Sheet



SPECIFICATION	VHF	900
Pager Type	Alphanumeric	Alphanumeric
Code Format	Flex	Flex
Baud Rate	1600 / 3200 / 6400	1600 / 3200 / 6400
Frequency Range	137 - 174 MHz	929 - 932 MHz
Alerting Sensitivity	1600 8.0 u/Vm	1600 8.0 u/Vm
	3200 11.0 u/Vm	3200 11.0 u/Vm
	6400 13.5 u/Vm	6400 13.5 u/Vm
Selectivity	55 dB	50 dB
Spur and Image Rejection	40 dB	40 dB
Frequency Stability	≤ ± 15 ppm	≤ ± 3.5 ppm
Channel Spacing	12.5 KHz / 25 KHz	
Receiver Type	Synthesized	
Programmable Addresses	16	
LCD Display	4 Lines, 20 Chars/Line - Zoom to 2 Lines, 10 Chars/Line	
Alert Tone SPL	≥ 78 dB @ 30 cm (12")	
Operating Temperature	+5 C to +40 C	
Storage Temperature	-40 C to +85 C	
Battery Type	"AA" Alkaline x 1	
	Auto Baud Detect	
Battery Life *	Collapse = 4	
	90 days	
Dimensions	81 X 55 X 18.5 mm (3.2 X 2.2 X 0.7 inch)	

* Estimate based on full capacity battery and 2 pages/day